



LED

LIGHTING PROGRAM

Performance LED

- High-Powered LEDs offer **True Replacement Performance**
- Suitable for both **Distance And Close-Range Uses**
- Optimal **Bright Light** for general lighting applications

Accent LED

- Suitable For **Short-Distance Illumination**
- Ideal As **Directional Accent Lighting**
- Perfect For **Highlighting Artwork/ No Color Fading**

MR16-GU10

Performance LED



EXN/HP/LED



MR16/GU10/HP/LED



3 LEDs

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR	LUMENS
EXN/HP/LED	3	4	LED MR16 Base, 12V	GX5.3	30,000	3000°K	180
MR16/GU10/HP/LED	3	4	LED GU10 Base, 120V	GU10	30,000	3000°K	150

THROW DISTANCE(m)	Photometrics		MR16/GU10 LED 3X1.33	35W GU10 HALOGEN 36°
	Beamwidth	Illuminance	Illuminance	Illuminance
1	55	310	500	
2	80	78	125	
3	117	35	55	

Accent LED



BPEXN/LED



BPMR16/GU10/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR
BPEXN/LED	21	<2	LED MR16 Base, 12V	GX5.3	30,000	3000°K
BPMR16/GU10/LED	21	<2	LED GU10 Base, 120V	GU10	30,000	3000°K

PAR20

Performance LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR	LUMENS
PAR20/HP/LED	3	5	LED PAR20 Reflector, 120V	Standard	30,000	3000°K	270



PAR20/HP/LED



Photometrics	PAR20 LED		PAR20 50w HALOGEN 30°
	Beamwidth	Illuminance	Illuminance
THROW DISTANCE(m)			
1	29	3595	1000
2	41	899	250
3	63	399	115

Accent LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR
BPPAR20/LED	21	<2	LED PAR20 Reflector, 120V	Standard	30,000	3000°K



BPPAR20/LED

PAR30

Performance LED



PAR30/L/HP/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR	LUMENS
PAR30/L/HP/LED	5	13	LED PAR30 Reflector, 120V	Standard	30,000	3000°K	490



Photometrics	PAR30 LED		PAR30 75w HALOGEN 30°
	Beamwidth	ILLUMINANCE	ILLUMINANCE
THROW DISTANCE(m)			
1	48	6739	2000
2	68	1685	500
3	80	749	225

Accent LED



BPPAR30/L/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR
BPPAR30/L/LED	36	<3	LED PAR30 Reflector, 120V	Standard	30,000	3000°K

PAR38

Performance LED



PAR38/HP/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR	LUMENS
PAR38/HP/LED	7	21	LED PAR38 Reflector, 120V	Standard	30,000	3000°K	725



7 LEDs

Photometrics THROW DISTANCE(m)	PAR38 LED		PAR38 90w HALOGEN 30°
	Beamwidth	Illuminance	Illuminance
1	45	8605	2200
2	75	2151	550
3	95	956	245

Accent LED



BPPAR38/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR
BPPAR38/LED	60	<3	LED PAR38 Reflector, 120V	Standard	30,000	3000°K

HOUSEHOLD

Performance LED



BPA19/HP/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR	LUMENS
BPA19/HP/LED	5	5	A19 Shape LED, 120V	Standard	30,000	3000°K	325

Accent LED



BPA19/LED

BPA15/LED

BPA15/CL/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR
BPA19/LED	34	<2	A19 Shape LED, 120V	Standard	30,000	3000°K
BPA15/LED	28	<2	A15 Shape LED, 120V	Standard	30,000	3000°K
BPA15/CL/LED	28	<2	Clear A15 Shape LED, 120V	Standard	30,000	3000°K

DECORATIVE

Accent LED Chandelier



BPCFC/LED BPCFF/LED BPEFC/LED BPEFF/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR
BPCFC/LED	28	<2	Clear Bent Tip, 120V	Candelabra	30,000	3000°K
BPCFF/LED	28	<2	Frost Bent Tip, 120V	Candelabra	30,000	3000°K
BPEFC/LED	28	<2	Clear Bent Tip, 120V	Standard	30,000	3000°K
BPEFF/LED	28	<2	Frost Bent Tip, 120V	Standard	30,000	3000°K

Accent LED Globe



BPG25/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS	COLOR
BPG25/LED	28	<2	White G25 Globe, 120V	Standard	30,000	3000°K
BPG25/CL/LED	28	<2	Clear G25 Globe, 120V	Standard	30,000	3000°K

Accent LED Night Lights



BPC7/LED BPC7/G/LED BPC7/R/LED BPC7/B/LED

SPECIFICATIONS

ITEM	LEDS	WATTAGE	DESCRIPTION	BASE	HOURS
BPC7/LED	3	<1	Cool White Night Light, 120V	Candelabra	50,000
BPC7/G/LED	3	<1	Green Night Light, 120V	Candelabra	50,000
BPC7/R/LED	3	<1	Red Night Light, 120V	Candelabra	50,000
BPC7/B/LED	3	<1	Blue Night Light, 120V	Candelabra	50,000



It's the bright thing to do.®



Accent LED

Performance LED

- 90% More Efficient Than Incandescent and Halogen
 - Long Lasting Up To 30,000 Hours
 - Mercury Free/ Environmentally Friendly
 - No UV Emissions
 - Resists Shock and Vibration
 - Cool Running and Silent
 - Instant On/ No Warm-Up Time
 - Rapid Cycling Capacity - Lifetime Not Shortened By Frequent On/Off Switching
 - Low Maintenance Costs

FEIT ELECTRIC COMPANY

4901 GREGG ROAD, PICO RIVERA, CA 90660

TELEPHONE: (562) 463-BULB (2852) • (800) 543-FEIT (3348) • FAX: (562) 908-6360

www.feit.com © 2009 FEIT ELECTRIC COMPANY, INC.

NOTE: Specifications are subject to change without notice. Please contact our customer service to verify specifications.

LLP0904